



NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

NOTES:

CONNECTIONS		
A	COMPRESSED AIR OUTLET	3/4" MALE
B	ELECTRICAL ENTRY	36.5 mm
C	OIL TANK DRAIN	1/2" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	1.4 m ³ /min
E	CONDENSATE DRAIN POINT	—
F	WEIGHT	185 KG

A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	I.K.	R.Ö.	02 MAR 07
REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE

THIS DRAWING IS THE PROPERTY OF ANKARA HAMAK IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HAMAK IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		ERS 5,5 COMPRESSOR DIMENSIONS	
FRACTIONS DECIMALS + — .X ± ANGELS .XX ± ± .XXX ±		DATE OF DRAWING 15 JAN 2007			
NEXT ASSY		ENGINEER B.ÖZKAN		CODE IDENT NO.	
USED ON		MANUFACTURING		SIZE A1	
APPLICATION		APPROVED R.ÖKÇÜN		DRAWING NO. 00-0055-9000	
		SCALE 1:5		UNIT WT _____ LB SHEET OF	

