



NOTES:

CONNECTIONS		
A	COMPRESSED AIR OUTLET	3/4" MALE
B	ELECTRICAL ENTRY	36.5 mm
C	OIL TANK DRAIN	1/2" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	1.4 m3/min
E	CONDENSATE DRAIN POINT	—
F	WEIGHT	195 KG

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	I.K.	R.Ö.	02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA HAMAK IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HAMAK IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		ERS 7,5 COMPRESSOR	
FRACTIONS DECIMALS + — .X ± ANGELS .XX ± ± .XXX ±		DATE OF DRAWING 15 JAN 2007			
DRAWING NO.		CHECKER I. KARAHAN		DIMENSIONS	
ENGINEER B. OZKAN		FUNCTIONAL DESIGN			
MANUFACTURING		WELDING		CODE IDENT NO.	
NEXT ASSY		USED ON		SIZE A1	
APPLICATION		APPROVED R. ÖKÇÜN		DRAWING NO. 00-0075-9000	
		SCALE 1:5		UNIT WT _____ LB SHEET OF	

