



NOTES:

CONNECTIONS		
A	COMPRESSED AIR OUTLET	1" MALE
B	ELECTRICAL ENTRY	36,5 mm
C	OIL TANK DRAIN	1/2" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	3,6 m ³ /min
E	CONDENSATE DRAIN POINT	—
F	WEIGHT	480

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

A	ADD TABULATION	TANK DRAIN	ELEC.NOTE	DATE	R.O.	02 MAR 07	
DESCRIPTIONS				DRAW	CHK'D	APPR.	DATE

THIS DRAWING IS THE PROPERTY OF ANADIRI HANCI INC. AND IS TRANSMITTED IN CONFIDENCE. NO OTHER RECEIPT FOR POSSESSION COPIES OR TRANSMISSION OF ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANADIRI HANCI INC.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON:		CONTRACT NUMBER		ERS 22 COMPRESSOR DIMENSIONS	
FRACTIONS	DECIMALS	DATE OF DRAWING	11 JAN 2007	DRAWING NO.	
± .XX ±	± .XX ±	DRAWN BY	CHECKER	SIZE	
ANGLES	.XX ±	V. SAKAL	I. KARAHAN	A1	
± .XXX ±	± .XXX ±	ENGINEER	FUNCTION GROUP	00-0220-9000	
		B. OZKAN		SCALE 1:1.5 UNIT WT LB SHEET OF	
NEXT ASSY USED ON APPLICATION		APPROVED R. OKÇON		SCALE 1:1.5 UNIT WT LB SHEET OF	

