



NOTES:

CONNECTIONS		
A	COMPRESSED AIR OUTLET	1" MALE
B	ELECTRICAL ENTRY	40 mm
C	OIL TANK DRAIN	1/2" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	3.6 m <sup>3</sup> /min
E	CONDENSATE DRAIN POINT	—
F	WEIGHT	587

NOTE:  
IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	I.K.	R.Ö.	02 MAR 07

  

THIS DRAWING IS THE PROPERTY OF ANKARA HAMAK IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HAMAK IND.					
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		<b>ERS 37 COMPRESSOR</b> <b>DIMENSIONS</b>	
FRACTIONS DECIMALS		DATE OF DRAWING			
± .X ±		11 JAN 2007			
± .XX ±		DRAFTSMAN	CHECKER		
± .XXX ±		V. SAKAL	I. KARAHAN	CODE IDENT NO.	
		ENGINEER	FUNCTIONAL DESIGN		
		B. OZKAN			
		MANUFACTURING	WELDING	SIZE	DRAWING NO.
				A1	00-0370-9000
NEXT ASSY	USED ON	APPROVED		SCALE	UNIT WT _____ LB SHEET OF
		R. ÖKÇÜN			