



NOTES:

CONNECTIONS		
A	COMPRESSED AIR OUTLET	1" MALE
B	ELECTRICAL ENTRY	40 mm
C	OIL TANK DRAIN	3/4 FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	9.2 m ³ /min
E	CONDANSATE DRAIN POINT	—
F	WEIGHT	845

NOTE:

IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTANENCE PURPOSES

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	I.K.	R.O.	02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA HAMAK IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HAMAK IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		ERS 45 COMPRESSOR	
FRACTIONS .X ±		DATE OF DRAWING			
ANGLES .XX ±		22 JAN 2007		DIMENSIONS	
± .XXX ±		DRAFTSMAN			
NEXT ASSY		V. SAKAL		I. KARAHAN	
USED ON		ENGINEER		FUNCTIONAL DESIGN	
APPLICATION		B. OZKAN		CODE IDENT NO.	
		MANUFACTURING		WELDING	
		APPROVED		SIZE	
		R. OKÇUN		A1	
				DRAWING NO.	
				00-0450-9000	
				SCALE 1:10	
				UNIT WT _____ LB SHEET OF _____	

