



NOTE:

IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

NOTES:

CONNECTIONS

A	COMPRESSED AIR OUTLET	1 1/4" MALE
B	ELECTRICAL ENTRY	58.5
C	OIL TANK DRAIN	3/4 FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	11 m ³ /min
E	CONDENSATE DRAIN POINT	—
F	WEIGHT	940

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	I.K.	R.Ö.	02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA HAMAK IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HAMAK IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		ERS 55 COMPRESSOR DIMENSIONS	
FRACTIONS DECIMALS		DATE OF DRAWING			
± — .X ±		11 JAN 2007			
± .XX ±		DRAFTSMAN	CHECKER		
± .XXX ±		V. SAKAL	I. KARAHAN		
		ENGINEER	FUNCTIONAL DESIGN	CODE IDENT NO.	
		B. OZKAN			
		MANUFACTURING	WELDING	SIZE	DRAWING NO.
				A1	00-0550-9000
NEXT ASSY	USED ON	APPROVED		SCALE	UNIT WT LB SHEET OF
	APPLICATION	R. OKÇUN			

