



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2"
B	ELECTRICAL ENTRY 58.5
C	OIL TANK DRAIN 3/4 FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 15.6 m <sup>3</sup> /min
E	CONDENSATE DRAIN POINT
F	WEIGHT 1350

NOTE:  
IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	L.K.	P.O.	02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA MAKAM IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHT TO REPRODUCE USE OR DISCLOSE IN WHOLE OR PART DATA CONTAINED HEREIN FOR ANY PURPOSE WITHOUT THE WRITTEN PERMISSION OF ANKARA MAKAM IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		DATE OF DRAWING		SIZE	
FRACTIONS	DECIMALS	11 JAN 2007		A1		DRAWING NO.	
± .X ±	± .XX ±	DRAFTSMAN V. SAKAL		CHECKER I. KARAHAN		00-0750-9000	
± .XXX ±	± .XXX ±	ENGINEER B. OZKAN		FACTORY REV#		CODE IDENT NO.	
				MANUFACTURING		WELDING	
APPROVED				R. OKGUN		SCALE	
NEXT ASSY				USED ON		UNIT WT	
APPLICATION				R. OKGUN		LB SHEET OF	