



NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 mm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2"
B	ELECTRICAL ENTRY 58.5
C	OIL TANK DRAIN 3/4 FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 22.8 m ³ /min
E	CONDENSATE DRAIN POINT
F	WEIGHT 1980

A	ADD TABULATION, TANK DRAIN, ELEC, NOTE	V.S.	LK	R.C.	02 MAR 07
REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE

THIS DRAWING IS THE PROPERTY OF ANKARA HANSA LTD AND IS TRANSMITTED IN CONFIDENCE. SEE YOUR RECEIPT FOR PERMISSION TO COPY OR TO TRANSFER ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HANSA LTD.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER	ERS 110 COMPRESSOR DIMENSIONS	
FRACTIONS	DECIMALS	DATE OF DRAWING	11 JAN 2007	
± .XX ±	± .XX ±	DRAWN BY	CHECKER	
ANGLES ± .XXX ±	± .XXX ±	ENGINEER	FUNCTIONAL DESIGN	
		ENGINEER	B. OZKAN	
		MANUFACTURING	WELDING	
		SIZE	DRAWING NO.	
		A0	00-1100-9000	
NEXT ASSY	USED ON	APPROVED	SCALE 1:10 UNIT MM LB SHEET OF	
APPLICATION		R. OKÇON		

