



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2" MALE
B	ELECTRICAL ENTRY 58,5 mm
C	OIL TANK DRAIN 3/4" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 23 m ³ /min
E	CONDANSATE DRAIN POINT —
F	WEIGHT 2150

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 90 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

A	ADD TABULATION, TANK DRAIN, ELEC,NOTE	Y.S.	LK.	P.O.	02 MAR 07
REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE

THIS DRAWING IS THE PROPERTY OF ANAKA HANNA INC. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFER OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANAKA HANNA INC.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CONTRACT NUMBER	
FRACTIONS	DECIMALS	DATE OF DRAWING	ERS 132 COMPRESSOR
± — .X ±		11 JAN 2007	DIMENSIONS
ANGLES ± .XX ±		DRAWN BY	CHECKER
± .XXX ±		V. SAKAL	I. KARAKALAN
		ENGINEER	FUNCTION DESIGN
		B. OZKAN	
		MANUFACTURING	WELDING
		APPROVED	SIZE
		R. OKÇON	A0
			DRAWING NO.
			00-1320-9000
			SCALE 1:10 UNIT #1 LB SHEET OF

NEXT ASSY	USED ON	APPLICATION

