



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 3" MALE
B	ELECTRICAL ENTRY 58,5 mm
C	OIL TANK DRAIN 3/4" FEMALE WITH FLOG
D	AIR COOLING FLOW RATE 23 m ³ /min
E	CONDANSATE DRAIN POINT
F	WEIGHT 3290

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 90 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

REV	DESCRIPTIONS	Y.S. DRAW	LK. CHK'D	P.O. APPR.	02 MAR 07 DATE
A	ADD TABULATION, TANK DRAIN, ELEC,NOTE				

THIS DRAWING IS THE PROPERTY OF ANAKA HANNA INC. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONVEYS OR TRANSFERS ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANAKA HANNA, INC.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CONTRACT NUMBER	
FRACTIONS	DECIMALS	DATE OF DRAWING	ERS 200 COMPRESSOR
± .X ±		11 JAN 2007	DIMENSIONS
ANGLES	.XX ±	DRAWN BY	CHECKER
± .XXX ±		V. SAKAL	I. KARALAN
		ENGINEER	FUNCTIONAL DESIGN
		B. OZKAN	
		MANUFACTURING	WELDING
		APPROVED	SIZE
		R. OKÇON	A0
			DRAWING NO.
			00-2000-9000
			SCALE 1:10
			UNIT #1
			LB
			SHEET
			OF

NEXT ASSY	USED ON	APPLICATION

