



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2"
B	ELECTRICAL ENTRY 58.5
C	OIL TANK DRAIN 3/4 FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 15.6 m ³ /min
E	CONDENSATE DRAIN POINT
F	WEIGHT 1400

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 mm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE		V.S.	L.K.	P.O.
					02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA MAKAM IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHT TO REPRODUCE USE OF OR DISCLOSE IN WHOLE OR PART DATA CONTAINED HEREIN FOR ANY PURPOSE WITHOUT THE WRITTEN PERMISSION OF ANKARA MAKAM IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER	
FRACTIONS	DECIMALS	DATE OF DRAWING	
± .X ±	± .XX ±	11 JAN 2007	
ANGLES	.XXX ±	DRAWN BY	CHECKER
± .XXX ±	± .XXX ±	V. SAKAL	I. KARAHAN
		ENGINEER	FACTORY SUPERVISOR
		B. OZKAN	

VSD 75 COMPRESSOR DIMENSIONS

SIZE	DRAWING NO.
A1	10-0750-9000

APPROVED: R. OKÇUN

SCALE: UNIT: WT: LB SHEET: OF: