



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2" MALE
B	ELECTRICAL ENTRY 58,5 mm
C	OIL TANK DRAIN 3/4" FEMALE WITH FLUG
D	AIR COOLING FLOW RATE 23 m <sup>3</sup> /min
E	CONDANSATE DRAIN POINT
F	WEIGHT 1750 KG

NOTE:  
 IT IS RECOMMENDED THAT A MINIMUM OF 90 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES.  
 -RECOMMENDED CLEARANCE DISTANCE MAX 3 m BEHIND DUCTING TO A WALL.

REV	DESCRIPTIONS	Y.S. DRAW	LK. CHK'D	P.O. APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC,NOTE				02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANAKA HANNA INC. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONVEYS OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANAKA HANNA, INC.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON

FRACTIONS	DECIMALS	CONTRACT NUMBER
± .XX ±	± .XX ±	11 JAN 2007
ANGLES	± .XXX ±	DRAWN BY: V. SAKAL
		CHECKER: I. KARADUMAN
		ENGINEER: B. OZKAN
		FUNCTION DESIGN:

**VORTEX COMPRESSOR**

DATE OF DRAWING	11 JAN 2007	<b>VSD 90 COMPRESSOR</b> DIMENSIONS
MANUFACTURING		
WELDING		CODE IDENT NO.
SIZE	A0	DRAWING NO.
APPROVED	R. OKÇON	10-0900-9000

SCALE 1:10 UNIT: mm LB SHEET OF