



NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 mm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2"
B	ELECTRICAL ENTRY 58.5
C	OIL TANK DRAIN 3/4 FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 22.8 m ³ /min
E	CONDENSATE DRAIN POINT
F	WEIGHT 2040

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC, NOTE	V.S.	LK	R.C.	02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA HANSA LTD AND IS TRANSMITTED IN CONFIDENCE. SEE YOUR RECEIPT FOR PERMISSION TO COPY OR TRANSMIT ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HANSA LTD.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON:

FRACCTIONS	DECIMALS	DATE OF DRAWING	VSD 110 COMPRESSOR
± .X ±	± .0005	11 JAN 2007	
ANGLES	.XX ±	DRAWN BY	DIMENSIONS
± .XXX ±	± .0005	V. SAKAL	
		CHECKER	
		ENGINEER	
		B. OZKAN	
		MANUFACTURING	
		WELDING	
		APPROVED	

CONTRACT NUMBER: _____
 CODE IDENT NO.: _____
 SIZE: **A0** DRAWING NO.: **10-1100-9000**
 SCALE 1:10 UNIT: mm LB SHEET OF _____

