



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 2" MALE
B	ELECTRICAL ENTRY 58,5 mm
C	OIL TANK DRAIN 3/4" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE 23 m3/min
E	CONDANSATE DRAIN POINT
F	WEIGHT 2550

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 90 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

A	ADD TABULATION, TANK DRAIN, ELEC,NOTE	Y.S.	LK.	P.O.	02 MAR 07
REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE

THIS DRAWING IS THE PROPERTY OF ANAKA HANNA INC. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONVEYS OR TRANSFERS ANY RIGHTS TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANAKA HANNA INC.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER	
FRACTIONS	DECIMALS	DATE OF DRAWING	VSD 160 COMPRESSOR DIMENSIONS
± .XX ±	± .XX ±	11 JAN 2007	
ANGLES	.XX ±	DRAFTER/ISSUER	V. SAKAL / I. KARALAN
± .XXX ±	± .XXX ±	ENGINEER	
		MANUFACTURING	ENGINEER
		BELDING	MANUFACTURING
		SIZE	DRAWING NO.
		A0	10-1600-9000
		APPROVED	SCALE 1:10 UNIT: mm LB SHEET OF
		R. OKÇON	

NEXT ASSY	USED ON
APPLICATION	

