



NOTES:

CONNECTIONS	
A	COMPRESSED AIR OUTLET 3" MALE
B	ELECTRICAL ENTRY 58,5 mm
C	OIL TANK DRAIN 3/4" FEMALE WITH FLOG
D	AIR COOLING FLOW RATE 23 m ³ /min
E	CONDANSATE DRAIN POINT
F	WEIGHT 3340

NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 90 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTENANCE PURPOSES

REV	DESCRIPTIONS	Y.S. DRAW	LK. CHK'D	P.O. APPR.	DATE
A	ADD TABULATION, TANK DRAIN, ELEC,NOTE				02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA HANNA INC. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONVEYS OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HANNA INC.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CONTRACT NUMBER	
FRACTIONS	DECIMALS	DATE OF DRAWING	VSD 200 COMPRESSOR DIMENSIONS
± .X ±	± .X ±	11 JAN 2007	
ANGLES ± .XX ±	± .XX ±	DRAFTER	CHECKER
± .XXX ±	± .XXX ±	V. SAKAL	I. KARALAN
		ENGINEER	FUNCTIONAL DESIGN
		B. OZKAN	
		MANUFACTURING	WELDING
		APPROVED	SIZE
		R. OKÇON	A0
			DRAWING NO.
			I0-2000-9000
			SCALE 1:10
			UNIT WT
			LB
			SHEET
			OF

NEXT ASSY	USED ON	APPLICATION

