



NOTE:
IT IS RECOMMENDED THAT A MINIMUM OF 60 cm CLEARANCE ON ALL SIDES AND ABOVE THE COMPRESSOR FOR MAINTANENCE PURPOSES

NOTES:

CONNECTIONS		
A	COMPRESSED AIR OUTLET	3/4" MALE
B	ELECTRICAL ENTRY	36.5 mm
C	OIL TANK DRAIN	1/2" FEMALE WITH PLUG
D	AIR COOLING FLOW RATE	2.1 m ³ /min
E	CONDANSATE DRAIN POINT	—
F	WEIGHT	387

25.05.2021

REV	DESCRIPTIONS	DRAW	CHK'D	APPR.	DATE
B	CHANGE DIM	V.S.	I.K.	R.Ö.	02 JAN 08
A	ADD TABULATION, TANK DRAIN, ELEC.NOTE	V.S.	I.K.	R.Ö.	02 MAR 07

THIS DRAWING IS THE PROPERTY OF ANKARA HAMAK IND. AND IS TRANSMITTED IN CONFIDENCE. NEITHER RECEIPT NOR POSSESSION CONFERS OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE, IN WHOLE OR PART, DATA CONTAINED HEREIN FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF ANKARA HAMAK IND.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NUMBER		ERS 15 COMPRESSOR DIMENSIONS	
FRACTIONS DECIMALS		DATE OF DRAWING			
± — .X ±		14 APR 2014			
ANGELS .XX ±		DRAFTSMAN	CHECKER		
± .XXX ±		V.SAKAL	I.KARAHAN	CODE IDENT NO.	
NEXT ASSY USED ON		ENGINEER	FUNCTIONAL DESIGN	SIZE DRAWING NO.	
APPL I C A T I O N		B.OZKAN	MANUFACTURING WELDING	A1 00-0150-9000	
		APPROVED		SCALE 1:5 UNIT WT LB SHEET OF	
		R.ÖKÇÜN			

